

TORQUE SPECIFICATION

Part tightened	N·m	kgf·cm	ft·lbf
Engine rear mounting x Transmission	25	250	18
Shift lever retainer x Transmission	19	195	14
Transmission x Engine	72	730	53
Starter x Transmission	39	400	29
Rear engine mounting member x Body	25	260	19
Rear engine mounting member x Transmission	13	135	10
Clutch cover x Flywheel	19	195	14
Service hole cover set bolt	12	120	9
Clutch release cylinder set bolt	12	120	9
Transmission shift lever x Control rod	19	195	14
Crossmember brace x Body	13	130	9
Heat insulator x Body	5.4	55	48 in.·lbf
Exhaust center pipe x Exhaust tail pipe	19	195	14
Exhaust front pipe x Exhaust center pipe	58	590	43
Pipe support bracket x Clutch housing	37	380	27
Exhaust front pipe x No.2 exhaust front pipe	58	590	43
Oxygen sensor set nut	20	200	14
Transmission shift lever x Shift lever retainer	7.8	80	69 in.·lbf
Release fork support x Transmission	26	260	19
Vehicle speed sensor set bolt	11	110	8
Companion flange lock nut	120	1,220	88
(Temporary tighten)	190	1,940	140
Front bearing retainer set bolt	10	100	7