

TORQUE SPECIFICATION

Part tightened		N·m	kgf·cm	ft·lbf
A/C compressor x Cylinder block	Stud bolt	26	265	19
	Bolt and nut	52	530	38
Oil pressure switch x Cylinder block		14	150	11
Drive belt tensioner Damper x Tensioner arm	2JZ-GTE M/T	20	200	14
Drive belt tensioner Damper x Drive belt tensioner bracket	2JZ-GTE M/T	20	200	14
Oil drain plug x No.2 oil pan		38	375	27
Oil pump body cover x Oil pump body		10	105	8
Plug x Oil pump body	2JZ-GE	49	500	36
	2JZ-GTE	29	300	22
Oil pump x Cylinder block		21	210	15
No.1 oil pan x Cylinder block	12 mm head	21	210	15
	14 mm head	39	400	29
Turbo oil outlet pipe (2JZ-GTE) x No.1 oil pan		27	280	20
Oil pan baffle plate x No.1 oil pan		8.8	90	78 in.·lbf
Oil strainer x No.1 oil pan		8.8	90	78 in.·lbf
No.2 oil pan x No.1 oil pan		8.8	90	78 in.·lbf
Oil level sensor x No.1 oil pan		5.4	55	48 in.·lbf
Drive belt tensioner bracket (2JZ-GTE M/T) x Oil pump		27	280	20
Crankshaft position sensor x Oil pump		8.8	90	78 in.·lbf
Oil cooler (2JZ-GTE) x Oil filter bracket		78	800	58
Oil nozzle (2JZ-GTE) x Cylinder block		8.8	90	78 in.·lbf