

TORQUE SPECIFICATION

Part tightened		N-m	kgf-cm	ft-lbf
Fuel line	for union bolt	29	300	22
	for flare nut	30	310	22
Fuel pressure regulator x Delivery pipe		8.8	90	78 in.-lbf
Fuel return pipe x Fuel pressure regulator		27	280	20
Delivery pipe x Intake manifold		21	210	15
Injector holder x Delivery pipe		7.8	80	69 in.-lbf
Fuel inlet pipe x Delivery pipe		41	420	30
Air intake chamber x Intake manifold		27	280	20
Manifold stay x Air intake chamber		39	400	29
Manifold stay x Cylinder head		39	400	29
EGR pipe x Cylinder head		27	280	20
EGR pipe x EGR valve		64	650	47
Control cable bracket x Air intake chamber		19	195	14
Air intake chamber stay x Intake manifold		19	195	14
Air intake chamber stay x Control cable bracket		19	195	14
Fuel pressure pulsation damper x Fuel pipe support		41	420	30
	for SST	35	350	25
Fuel tank band x Body		39	400	29
MAF meter x Air cleaner case		6.9	70	61 in.-lbf
Throttle body x Air intake chamber		21	210	15
IAC valve x Air intake chamber		21	210	15
EGR gas temperature sensor x EGR valve		20	200	14
Knock sensor x Cylinder block		44	450	33
Main heated oxygen sensor x Exhaust manifold		20	200	14
Sub heated oxygen sensor x Center exhaust pipe		20	200	14
Upper front crossmember extension x Front suspension	Bolt	29	300	22
	Nut	33	340	25
Front lower arm bracket stay x Front suspension	Bolt	44	450	33
	Nut	59	600	43